

LT70/LTM70-CB



WITH HIGH FREQUENCY
高频

MACHINE TORCH
自动枪

1/8G

1/4G

M14X1

M16X1.5

22 Central adaptor
中央插头

19

21

23

Technical Data	技术参数	
Current 额定电流	70 Amp	
Duty Cycle 占载率	60%	
Gas 气体	AIR 空气	
Gas Pressure 气压	4.5-5.0 Bar	
Gas Flow 气流量	130LPM	
Ignition 引弧方式	HF 高频	
Post Flow 气体延时	70 sec. recommended 推荐70秒	
Standard Length 标准长度	6M	



HAND TORCH

Code	Ref	Description
IVT6870	1564	Plasma cutting torch LT70/6m 1/8G;等离子切割枪/LT70/6m 1/8G
IVT6876		Plasma cutting torch LT70/6m M14x1;等离子切割枪/LT70/6m/M14x1
IVT6879		Plasma cutting torch LT70/6m M14x1;等离子切割枪/LT70/6m/M14x1
IVT6875		Plasma cutting torch LT70/6m M16x1.5;等离子切割枪/LT70/6m/M16x1.5
IVT6877	1573	Plasma cutting torch LT70/6m central adaptor;等离子切割枪/LT70/6m/中央插头

MACHINE TORCH

Code	Ref	Description
IVT6740	1563	Plasma cutting auto torch LTM70/6m 1/8G;等离子自动切割枪/LTM70/6m 1/8G
IVT6742		Plasma cutting auto torch LTM70/6m 1/4G;等离子自动切割枪/LTM70/6m 1/4G
IVT6743		Plasma cutting auto torch LTM70/6m M14x1;等离子自动切割枪/LTM70/6m/M14x1
IVT6744		Plasma cutting auto torch LTM70/6m M16x1.5;等离子自动切割枪/LTM70/6m/M16x1.5
IVT6746	1566	Plasma cutting auto torch LTM70/6m central adaptor;等离子自动切割枪/LTM70/6m/中央插头

Position	Code	Ref	Description
1	ISM6662	1405	Double pointed spacer/LT70;两点支架 LT70
2	ISM0060	1394	Spacer spring/LT70;隔离环 LT70
3	ISM0007		Shield cap for Extended tip/LT70;长接触切割保护帽 LT70
4			Outside nozzle;外喷嘴
4.1	IVS0087-03	5.710.171	Outside nozzle LT70;外喷嘴 LT70
4.2	IVS0087-01		Outside nozzle/maximum life LT70;外喷嘴/长寿命 LT70
5			Tip;喷嘴
5.1	IVU0065-09	1309	Tip Φ 0.9mm LT50-70;喷嘴 Φ 0.9mm/ LT50-70
5.2	IVU0033-10	1396	Tip Φ 1.0mm LT50-70;喷嘴 Φ 1.0mm/ LT50-70
5.3	IVU0033-11		Tip Φ 1.1mm LT50-70;喷嘴 Φ 1.1mm/ LT50-70
5.4	IVU0033-12	1395/L	Tip Φ 1.2mm LT50-70;喷嘴 Φ 1.2mm/ LT50-70
6			Tip;喷嘴
6.1	IVU0028-10		Flat tip Φ 1.0mm;扁平喷嘴 Φ 1.0mm/ LT50-70
6.2	IVU0028-12		Flat tip Φ 1.2mm;扁平喷嘴 Φ 1.2mm/ LT50-70
7			Tip;喷嘴
7.1	IVU0064-10	1305	Conical tip Φ 1.0mm/LT50-70;锥形喷嘴 Φ 1.0mm/ LT50-70
7.2	IVU0064-12		Conical tip Φ 1.2mm/LT50-70;锥形喷嘴 Φ 1.2mm/ LT50-70
8			Tip;喷嘴
8.1	IVU0035-98	1366	Extended tip Φ 0.98mm/LT50-70;加长喷嘴 Φ 0.98mm/ LT50-70
8.2	IVU0018-10	1395	Extended tip Φ 1.0mm/LT50-70;加长喷嘴 Φ 1.0mm/ LT50-70
8.3	IVU0018-11		Extended tip Φ 1.1mm/LT50-70;加长喷嘴 Φ 1.1mm/ LT50-70
8.4	IVU0018-12		Extended tip Φ 1.2mm/LT50-70;加长喷嘴 Φ 1.2mm/ LT50-70
9	IVF0002		Diffuser/LT50-70;分流器 LT50-70
10	IVB0018	1402	Electrode HF Plasma LT70;等离子电极 LT70
11	IVB0019	1368	Extended electrode HF Plasma LT70;加长等离子电极 LT70
12	IZN0766	3.065.204	Air tube/LT70;导流管 LT70
13	IVZ0015	1071	Plasma torch head LT70;等离子枪头 LT70
13a	IFT0707		"O"ring Φ 12.42x1.78mm in silicon red;O型圈 Φ 12.42x1.78mm/硅胶/红色
14	IGV0039		Plasma handle manual/CB50-70/Red;等离子手柄/CB50-70/红色
15	IHJ0722		Protection part/Plasma/Yellow;开关保护档片/等离子用/黄色
16	IHQ0070	185.0031	Trigger;开关
17	IHJ0893		Joint/small/new type;球节套件/小/新式
18			Cable assembly;电缆组
18.1	IVN0006066-00		Cable assembly/LT50-70/6MMQ/6M ATT.1/8G;电缆组/LT50-70/6MMQ/6M ATT.1/8G
18.2	IVN0006066-00		Cable assembly/LT50-70/6MMQ/6M center adaptor;电缆组/LT50-70/6MMQ/6M中央插头
18.3	IVN10006066-00		Cable assembly/LTM50-70/6MMQ/6M central adaptor;电缆组/LTM50-70/6MMQ/6M中央插头
18.4	IVN10006066-00		Cable assembly/LTM50-70/6MMQ/6M ATT.1/8G;电缆组/LTM50-70/6MMQ/6M ATT.1/8G
18.5	IVN0628		Cable assembly/LT50-70/6m central adaptor;电缆组/LT50-70/6m/中央插头
19	ICG6006	60368	Spanner for Plasma;等离子枪扳手
20	IVZ0073	1349	Plasma torch head LTM70;等离子枪头 LTM70
20a	IGV0013		Fiber glass position tube/LTM;自动枪手柄 LTM
21			Cable assembly LTM;电缆组 LTM
21.1	IZT5687		Connecting adaptor 1/8G-1/4G;转换接头1/8G-1/4G
21.2	IZT5688		Connecting adaptor 1/8G-M14x1;转换接头1/8G-M14x1
21.3	IZT5689		Connecting adaptor 1/8G-M16x1.5;转换接头1/8G-M16x1.5
22	IZX0078		Central adaptor torch side Plasma 5 pins;等离子中央插头/5针
23	ISM0029		Circle cutting attachment/LT70;圆周切割附件 LT70

Link Welding Technology Co., Limited

Add:Rm. 19C, Lockhart Ctr., 301-307 Lockhart Rd., Wan Chai, Hong Kong.

Tel: +00852-6735 8659 Fax:+00852-3114 9072 Email : info@linkwelding.com

Link Welding Technology Co., Limited

Add:Rm. 19C, Lockhart Ctr., 301-307 Lockhart Rd., Wan Chai, Hong Kong.

Tel: +00852-6735 8659 Fax:+00852-3114 9072 Email : info@linkwelding.com